

AKROPRIME WOOD PRIMER

PRODUCT DESCRIPTION

Akroprime Wood Primer is designed specifically for use on interior and exterior, hard and soft wood before applying a paint topcoat. **Akroprime Wood Primer** provides excellent penetration and sealing properties on wood and provides a good bond for subsequent coats of paint.

SPECIFICATIONS

Prepare substrate by removing all loose material, dirt and grease etc. Ensure that surface to be painted is completely dry. Sand substrate thoroughly and remove all dust.

APPLICATION

Akroprime Wood Primer can be applied by brush, roller, or airless spray. Thinning is not recommended. Do not apply at temperatures below 10 °C, or above 45 °C, or a RH above 80%. Product is ready for use by brush or roller. Apply a full even coat.

TECHNICAL DATA

• Colour	White, Pink
• Volume Solids	Approx. 70 % by mass; 60 % by volume
• Drying Time	16 hrs @ 23 °C
• Overcoating Time	16 hrs @ 23 °C
• Spreading Rate	15 m ² /ℓ per coat at 40 µm DFT
• DFFT @10 sqm/lt	6 to 9 square metres per litre per coat
• Recommended DFFT	40 microns; recommended system: 100 microns
• Solvent for Cleaning	Water

HEALTH AND ENVIRONMENT

There is no health risk involved in handling **Akroprime Wood Primer**. Spillages and splashes may be removed with clean water. Avoid spillages into main water supply or landfills; consult your local authority for information on the disposal of spillages.

GENERAL

This information is shared in good faith, is based on our present state of knowledge, and is subject to technological upgrades or advances. We cannot guarantee the performance of our products as we have little or no control over their end use. We do, however, warrant that if used as recommended, the product will perform as specified or expected.

Tel: 086 111 4442 | 35 Jan Smuts Rd, Beaconvale, Cape Town | Email: info@olympiapaints.co.za | www.olympiapaints.co.za

