

AKROSHEEN SATIN SHEEN PURE ACRYLIC

PRODUCT DESCRIPTION

Akrosheen Satin Sheen Pure Acrylic Coating is a superior quality coating for interior and exterior use based on a pure acrylic polymer and is reinforced with proprietary pigments and additives. **Akrosheen** is characterised by having outstanding long-term durability, outstanding UV resistance, excellent adhesion and local flexibility, and is extremely washable and may be used for internal and external wall surfaces, roofs and suitably primed timber and metals. **Akrosheen** complies with the requirements of **SABS 1586 Grade 1**. Akrosheen is APEO and heavy metal and lead free and has a low VOC (< 12g/ltr).

SPECIFICATIONS

New Work - Masonry and fibre cement substrates: Prepare substrate by removing all dirt, grime and loose adherent matter. Prime external substrates with **Akroprime AR Masonry Primer**. Prime internal substrates with **Supercover Acrylic Primer**, then apply 2 coats of **Akrosheen Satin Sheen Pure Acrylic Coating**. **Refurbishment** - Prepare by removing all loose and friable matter, and loose and flaking paint. Apply 1 coat **Akroprime AR Masonry Primer**, and 2 coats **Akrosheen Satin Sheen Pure Acrylic Coating**. **Timber and Metal Substrates** - Apply 1 coat appropriate primer, and 2 coats **Akrosheen Satin Sheen Pure Acrylic** coating.

APPLICATION

Akrosheen is supplied Ready for Use. Dilution is not recommended except as directed. Apply by brush, roller, or airless spray, ensuring that no air voids are produced during application. **Akrosheen** should not be applied at temperatures below 5 °C, and above 45 °C, or above 80% relative humidity, or 2 °C above the dew point.

TECHNICAL DATA

• Colour	All colours
• Volume Solids	42 % +/- 1
• Drying Time	2 hrs @ 25 °C & 50 % RH
• Over coating Time	4 to 6 hrs (if drying time is adhered to per above)
• Spreading Rate	7 to 10 square metres per litre per coat
• DFT @ 10 sqm/ltr	40 microns
• Recommended DFT	100 microns min. (for total system)
• Solvent for cleaning	Water

HEALTH AND ENVIRONMENT

There is no health risk involved in handling **Akrosheen Satin Sheen Pure Acrylic**. Spillages and splashes may be removed with clean water. Avoid spillages into main water supply or landfills; consult your local authority for information on the disposal of spillages.

GENERAL

This information is shared in good faith, is based on our present state of knowledge, and is subject to technological upgrades or advances. We cannot guarantee the performance of our products as we have little or no control over their end use. We do, however, warrant that if used as recommended, the product will perform as specified or expected.

Tel: 086 111 4442 | 35 Jan Smuts Rd, Beaconvale, Cape Town | Email: info@olympiapaints.co.za | www.olympiapaints.co.za

