

## AKROTEC 99 SUPER ADHESION COATING

### PRODUCT DESCRIPTION

**Akrotec 99 Super Adhesion Coating** is a high-build coating based on a pure acrylic polymer and is reinforced with an antifungal additive and a proprietary polypropylene fibre. **Akrotec 99 Super Adhesion Coating** is characterised by having outstanding waterproofing, long term durability, UV resistance, excellent adhesion, and local flexibility. **Akrotec 99** may be used to waterproof and seal walls, parapets and for roof flashings.

### SPECIFICATIONS

Prepare substrate by removing all dirt, grime and loose adherent matter. Prime friable surfaces with **Akroprime Masonry Primer**. Apply 2 coats of **Akrotec 99 Super Adhesion Coating** to walls, parapets, etc., as supplied. To waterproof flashing details, encapsulate the Polyester Waterproofing Membrane with **Akrotec**, and apply 2 coats of **Akrotec** as finishing coats.

### APPLICATION

**Akrotec** is supplied Ready for Use. Thinning is not recommended at all. Apply by brush, roller, or airless spray, ensuring that no air voids are produced during application. For flashing details ensure that the membrane is completely saturated with **Akrotec** before the application of topcoats.

### TECHNICAL DATA

• Colour	All colours
• Volume Solids	42 % +- 1
• Drying Time	2 hrs @ 25 °C & 50 % RH
• Overcoating Time	4 to 6 hrs (if drying time is adhered to per above)
• Spreading Rate	4 to 6 square metres per litre per coat
• DFFT @ 5 sqm/lt	80 microns
• Recommended DFFT	150 microns min. (for total system)
• Solvent for Cleaning	Water

### HEALTH AND ENVIRONMENT

There is no health risk involved in handling **Akrotec 99 Super Adhesion Coating**. Spillages and splashes may be removed with clean water. Avoid spillages into main water supply or landfills; consult your local authority for information on the disposal of spillages.

### GENERAL

This information is shared in good faith, is based on our present state of knowledge, and is subject to technological upgrades or advances. We cannot guarantee the performance of our products as we have little or no control over their end use. We do, however, warrant that if used as recommended, the product will perform as specified or expected.

Tel: 086 111 4442 | 35 Jan Smuts Rd, Beaconvale, Cape Town | Email: [info@olympiapaints.co.za](mailto:info@olympiapaints.co.za) | [www.olympiapaints.co.za](http://www.olympiapaints.co.za)

