

AKROTEX COURSE TEXTURED ACRYLIC

PRODUCT DESCRIPTION

Akrotex Course Textured Acrylic Coatings are aqueous high-build textured coatings based on specific novel acrylic polymers, reinforced with a proprietary film fungicide and naturally occurring micaceous and marble minerals that together produces a tough high-quality coating with exceptional exterior durability. Akrotex is further reinforced with a proprietary medium strand cellulose fibre to improve coating strength and bridging properties. **Akrotex Course Textured Acrylic Coatings** may be used on internal and external masonry, soffits, ceilings, composition boards, suitably prepared and primed wood and metals.

SPECIFICATIONS

Prepare substrate by removing all dirt and loose adherent matter. Apply 1 coat Akrotex Primer, and 2 coats **Akrotex Course Textured Acrylic Coating** by brush, roller, trowel or spray to desired pattern. **Optional:** Overcoat **Akrotex Course Textured Acrylic Coating** with 2 coats of **Akrosheen Midsheen Pure Acrylic Coating** or **Akrocote Matt Pure Acrylic Coating** to improve dirt resistance of the coating system.

USE AND APPLICATION

Akrotex Course Textured Acrylic Coating is supplied ready for use, and is applied as follows:

- **Raked Finish:** Apply Akrotex Tuscan Coating by roller and finish off vertically using a block brush or broom to desired pattern.
- **Tyrolean Stipple Finish:** Apply Akrotex Tuscan Coating by hopper gun to desired pattern.
- **Stippled Finish:** Apply Akrotex Tuscan Coating by wool roller and finish off using a stipple roller to desired pattern.

TECHNICAL DATA

- | | |
|------------------------------|---|
| • Colour | Range |
| • Coating Thicknesses | 0, 5 to 2 mm |
| • Volume Solids | 55 to 60 % +- 1 |
| • Drying Time | 2 hours @ 25 °C & 50 % RH |
| • Over coating Time | 12 to 24 hours (if drying time is adhered to per above) |
| • Spreading Rate | 1 to 4 square metres/litre depending on texture |
| • Shelf Life | 12 months in unopened container |

HEALTH AND ENVIRONMENT

There is no health risk involved in handling **Akrotex Course Textured Acrylic Coatings**. Spillages and splashes may be cleaned off with clean water. Avoid spillages into main water supply or landfills. Consult your local authority for information on the disposal of spillages.

GENERAL

This information is shared in good faith, is based on our present state of knowledge, and is subject to technological upgrades or advances. We cannot guarantee the performance of our products as we have little or no control over their end use. We do, however, warrant that if used as recommended, the product will perform as specified or expected.

Tel: 086 111 4442 | 35 Jan Smuts Rd, Beaconvale, Cape Town | Email: info@olympiapaints.co.za | www.olympiapaints.co.za

