

AKROTEX FINE TEXTURED ACRYLIC

PRODUCT DESCRIPTION

Akrotex Fine Textured Acrylic Coatings is an aqueous high build textured coating based on specific novel acrylic polymers, reinforced with a proprietary film fungicide and naturally occurring micaceous and marble minerals that together produces a tough high-quality coating with exceptional exterior durability. Akrotex is further reinforced with a proprietary medium strand cellulose fibre to improve coating strength and bridging properties. **Akrotex Fine Textured Acrylic** may be used on internal and external masonry, soffits, ceilings, composition boards, suitably prepared and primed wood and metals.

SPECIFICATIONS

Prepare substrate by removing all dirt, and loose adherent matter. Apply 1 coat **Akrotex Primer**, and 2 coats **Akrotex Fine Textured Acrylic** by brush, roller, trowel or spray to desired pattern. **Optional:** Overcoat **Akrotex Fine Textured Acrylic** with 2 coats of **Akrosheen Midsheen Pure Acrylic Coating** or **Akrocote Matt Pure Acrylic Coating** to improve dirt resistance of the coating system.

APPLICATION

Akrotex Fine Textured Acrylic is supplied ready for use, and is applied as follows:

- **Raked Finish**
Apply **Akrotex Fine Textured Acrylic** by roller and finish off vertically using a block brush or broom to desired pattern.
- **Tyrolean Stipple Finish**
Apply **Akrotex Fine Textured Acrylic** by hopper gun to desired pattern.
- **Stippled Finish**
Apply **Akrotex Fine Textured Acrylic** by wool roller and finish off using a stipple roller to desired pattern.

TECHNICAL DATA

- | | |
|-------------------------------|---|
| • Colour | Range |
| • Coating Thicknesses | 0, 5- to 2 mm |
| • Volume Solids | 55 to 60 % +- 1 |
| • Drying Time | 2 hours @ 25 °C & 50 % RH |
| • Over coating Time | 12 to 24 hours (if drying time is adhered to per above) |
| • Spreading Rate | 1 - 4 square metres/litre depending on texture |
| • Solvent for cleaning | Water |
| • Shelf Life | 12 months in unopened container |

HEALTH AND ENVIRONMENT

There is no health risk involved in handling **Akrotex Fine Textured Acrylic**. Spillages and splashes may be removed with clean water. Avoid spillages into main water supply or landfills. Consult your local authority for information on the disposal of spillages.

GENERAL

This information is shared in good faith, is based on our present state of knowledge, and is subject to technological upgrades or advances. We cannot guarantee the performance of our products as we have little or no control over their end use. We do, however, warrant that if used as recommended, the product will perform as specified or expected.

Tel: 086 111 4442 | 35 Jan Smuts Rd, Beaconvale, Cape Town | Email: info@olympiapaints.co.za | www.olympiapaints.co.za

