

# Technical Bulletin

# MARBLEPLAST GRANULAR COATINGS

#### **PRODUCT DESCRIPTION**

**Marbleplast Granular Coating** is a range of natural aggregate granular plasters suitable for interior and exterior use. **Marbleplast Granular Coating** has exceptional durability and is available in a range of colours, thicknesses, and textures.

#### **SPECIFICATIONS**

#### **Product Features:**

- Sand textured finish
- Protects exterior surfaces against the weather and the elements
- Durable and long lasting
- Fills hairline cracks and disguises minor surface defects and repaired areas
- Can be applied directly to sound cement surfaces

#### **APPLICATION**

**Marbleplast Granular Coating** is supplied Ready for Use. Dilution is not recommended. Apply by brush, roller or spray to a consistent coating thickness.

#### **TECHNICAL DATA**

Colour RangeVolume Solids 70 % +- 1

• **Drying Time** 4 hours @ 25 °C & 50 % RH

• Over coating Time 12 to 24 hours (if drying time is adhered to per above)

Spreading Rate 4 to 6 sqmSolvent for Cleaning Water

• Shelf Life 12 months in unopened container

### **HEALTH AND ENVIRONMENT**

There is no health risk involved in handling **Marbleplast Granular Coatings**. Spillages and splashes may be removed with clean water. Avoid spillages into main water supply or landfills. Consult your local authority for information on the disposal of spillages.

### **GENERAL**

This information is shared in good faith, is based on our present state of knowledge, and is subject to technological upgrades or advances. We cannot guarantee the performance of our products as we have little or no control over their end use. We do, however, warrant that if used as recommended, the product will perform as specified or expected.



ISO 9001





Tel: 086 111 4442 | 35 Jan Smuts Rd, Beaconvale, Cape Town | Email: info@olympiapaints.co.za | www.olympiapaints.co.za

BBBEE VERIFIED