

WOODGLOW EXTERIOR WOOD VARNISH

PRODUCT DESCRIPTION

Woodglow Exterior Varnish is a long oil alkyd-based transparent coating containing Ultraviolet absorbing Iron Oxide pigments which together provides superior exterior durability, water resistance and overcoating properties. Woodglow produces a semi-gloss finish. **Woodglow Exterior Varnish** is suitable for interior and exterior use for all types of timber and composite boards and is available in a range of standard colours.

SPECIFICATIONS

Prepare substrate by removing all loosely adherent material etc. Sand down to remove all raised grain, etc. Apply 1 coat of **Woodglow Exterior Varnish** thinned 10% with Mineral Turpentine as a sealer, sand lightly to remove any raised grain and apply 2 coats **Woodglow Exterior Varnish** as supplied.

APPLICATION

Woodglow Exterior Varnish is supplied Ready for Use by brush, roller, or conventional or airless spray. Thinning is not recommended, except as directed, when a maximum reduction of 10% with mineral turpentine by volume is recommended, this only for very dry and porous surfaces. Do not apply at temperatures below 10 °C, or above 45 °C, Or a RH above 80%.

TECHNICAL DATA

- **Colour** Clear, Pale Clear, Light Oak, Mahogany, Teak
- **Volume Solids** 35 % +- 1
- **Drying Time, Surface** 2 hours @ 25 °C & 50 % RH
- **Overcoating Time** 12 to 16 hours (if drying time is adhered to per above)
- **Spreading Rate** 12 - 15 square metres per litre per coat
- **DFFT @ 10sqm/lt** 25 microns
- **Recommended DFT** 75 microns min. of total system
- **Solvent for cleaning** Mineral Turpentine

HEALTH AND ENVIRONMENT

Woodglow Exterior Varnish contains ingredients that are harmful to mammalian tissue through prolonged contact or ingestion. Solvent fumes are known to affect mucous membranes. Use gloves and appropriate respirators when applying the coating. Wash skin spillages immediately with soap and water. If irritation persists, consult a physician. Consult your local authority regarding the disposal of spillages.

GENERAL

This information is shared in good faith, is based on our present state of knowledge, and is subject to technological upgrades or advances. We cannot guarantee the performance of our products as we have little or no control over their end use. We do, however, warrant that if used as recommended, the product will perform as specified or expected.

Tel: 086 111 4442 | 35 Jan Smuts Rd, Beaconvale, Cape Town | Email: info@olympiapaints.co.za | www.olympiapaints.co.za

