

## AKROCOTE MATT PURE ACRYLIC COATING

### PRODUCT DESCRIPTION

**Akrocote Matt Pure Acrylic Coating** is a high-quality matt aqueous coating and is suitable for interior and exterior use, is based on a pure acrylic copolymer, and is reinforced with a proprietary antifungal additive. **Akrocote** is characterised by its outstanding long-term durability, UV resistance, excellent adhesion and local flexibility, and is extremely washable.

**Akrocote** may be used both internally and externally on all suitably-prepared and primed substrates. **Akrocote** is particularly suited for use where resistance to fungal growth is desired. **Akrocote** conforms to the requirements of SANS 1586:2007 Grade 11. **Akrocote** is APEO and heavy metal free, and has a low VOC.

### SPECIFICATIONS

Prepare substrate by removing all dirt, grime, and loosely adherent matter. Prime friable surfaces with **Akroprime AR Masonry Primer**. For normal sound surfaces, prime with 1 coat **Supercover Acrylic Primer**, then apply 2 coats of **Akrocote Matt Pure Acrylic** to colour as supplied.

### APPLICATION

**Akrocote** is supplied ready for use. Thinning is not recommended at all. Apply by brush, roller or airless spray, ensuring that no air voids are formed in its application. **Akrocote** should not be applied at temperatures below 5 deg C, and above 45 deg C, above 80% relative humidity, or 2 deg C above dew point.

### TECHNICAL DATA

• Colour	All colours
• Volume Solids	42 % +- 1
• Drying Time	2 hrs @ 25 °C& 50 % RH
• Overcoating Time	4 to 6 hrs (if drying time is adhered to per above)
• Spreading Rate	6 to 8 square metres per litre per coat
• DFT @ 10 sqm/lt	40 microns
• Recommended DFT	100 microns min. (for total system)
• Solvent for cleaning	Water

### HEALTH AND ENVIRONMENT

There is no health risk involved in handling **Akrocote Matt Pure Acrylic**. Spillages and splashes may be removed with clean water. Avoid spillages into main water supply or landfills. Consult your local authority for information on the disposal of spillages.

### GENERAL

This information is shared in good faith, is based on our present state of knowledge, and is subject to technological upgrades or advances. We cannot guarantee the performance of our products as we have little or no control over their end use. We do, however, warrant that if used as recommended, the product will perform as specified or expected.

Tel: 086 111 4442 | 35 Jan Smuts Rd, Beaconvale, Cape Town | Email: [info@olympiapaints.co.za](mailto:info@olympiapaints.co.za) | [www.olympiapaints.co.za](http://www.olympiapaints.co.za)

